

Standalone 960H DVR

Model #: 960H-DVR4



Features

- H.264 video compression
- WD1/960H resolution recording
- HDMI and VGA output at up to 1920×1080P resolution
- Dual-stream
- Up to 4-ch synchronous playback
- HDD quota and group management
- NTP, SMTP, NFS, UPnP and iSCSI protocols

Technical Specifications

Model No.	DVR0404-960H
Video/Audio input	
Video compression	H.264
Video input	4-ch
Video input interface	BNC (1.0 Vp-p, 75 Ω), PAL / NTSC self-adaptive
Audio compression	G.711u
Audio input	1-ch
Two-way audio input	RCA
Video /Audio output	
HDMI Output	1-ch, resolution: 1920 × 1080P / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), Resolution: PAL: 704 × 576, NTSC: 704 × 480
VGA Output	1-ch, resolution: 1920×1080P/60Hz,1280×1024/60Hz,1280×720/60Hz, 1024×768/60Hz
Recording resolution	WD1/960H/D1/4CIF/2CIF/CIF/QCIF
Frame rate	30 FPS real time
Video bit rate	32 Kbps ~ 2048 Kbps, or user defined (Max. 3072 Kbps)
Audio output	1-ch, RCA (Linear, 1 kΩ)
Audio bit rate	64 Kbps
Dual-stream	Support; Sub-stream: CIF / QCIF @ 30 fps /N)
Stream type	Video, Video & Audio
Synchronous playback	4-ch
Hard Disk	
SATA	1 SATA interfaces
Capacity	Up to 4TB capacity for each disk
External interface	
Network interface	1, RJ45 10M / 100M Ethernet interface
Web Browser	IE 7, IE 8, IE 9, Chrome 8 +, Firefox 3.5 +, Safari 5 +
Serial interface	1; standard RS-485 serial interface, half-duplex
USB interface	2, USB2.0
General	
Power supply	12V DC
Consumption	≤ 10 W
Working temperature	14 °F ~ 131 °F
Working humidity	10% ~ 90%
Chassis	Standalone 1U chassis
Dimensions	315 × 230 × 45 mm
Weight	≤ 2 kg



1. Video in
2. Video out
3. USB interface
4. HDMI Interface
5. VGA Interface
6. Audio in, RCA connector
7. Audio out, RCA connector
8. LAN network interface
9. RS-485 serial interface
10. 12VDC power input
11. Power switch
12. GND

For more information please contact Protection Depot
Toll Free: 1-877-669-6368 - Email: sales@protectiondepot.com