

**Standalone HDCVI DVR
Model # DVR5116-CVI**



Features

- Up to 16 cameras with 1080p realtime preview
- All channel 720P live & recording
- H.264 dual-stream video compression
- HDMI and VGA output at up to 1920x1080P resolution
- Up to 16 channel synchronous realtime playback
- Support 2 SATA HDD up to 8TB, 2 USB2.0

Technical Specifications

Model No.	DVR5116-CVI
Video/Audio input	
Video/Audio compression	H.264 /G.711u
Video input	16-ch
Video input interface	BNC (1.0 Vp-p, 75 Ω), PAL / NTSC self-adaptive
Audio input	4 channel, BNC
Audio Two way Talk	Reuse audio input/output channel 1
Video /Audio output	
HDMI output	1-ch, resolution: 1920 x 1080P / 60 Hz ,1280 x 1024 / 60 Hz, 1280 x 720 / 60 Hz, 1024 x 768 / 60 Hz
VGA output	1-ch, resolution: 1920x1080P/ 60Hz,1600x1200/ 60Hz,1280x1024/ 60Hz, 1280x720/ 60Hz, 1024x768/ 60Hz
Encoding resolution	720P(1280x720/1280x600)/960H(960x576/960x480)/D1 4CIF(704x576/704x480)/CIF(352x288/352x240) QCIF(176x144/176x120)
Resolution Record	Main Stream: 720P/960H/D1/HD1/2CIF/CIF(1~25/30fps) Sub Stream: CIF/QCIF(1~25/30fps)
Audio output	1 channel, BNC
Audio bit rate	48~6144Kb/s
Dual-stream	Support; Sub-stream: CIF / QCIF (1 ~ 25/30fps)
Stream type	Video, Video & Audio
Synchronous playback	16-ch
Hard Disk	
SATA	2 SATA ports
Capacity	Up to 8TB capacity
External interface	
Network interface	1, RJ45 10M / 100M Ethernet interface
Web Browser	IE 7, IE 8, IE 9, Chrome 8 +, Firefox 3.5 +, Safari 5 +
Serial interface	1 RS232 (For PC Communication and Keyboard) 1 RS485 (For PTZ control)
USB interface	2 ports(1 Rear), USB2.0
General	
Power supply	DC12V/2A
Consumption	15W(without HDD)
Working temperature	14 °F ~ 131 °F
Working humidity	10% ~ 90%
Dimensions	375mm x 285mm x 45mm
Weight	2.35KG(without HDD)

Rear Panel



1. Video in
2. Video out
3. USB interface
4. HDMI Interface
5. VGA Interface
6. Audio in, RCA connector
7. Audio out, RCA connector
8. LAN network interface
9. RS-485 serial interface
10. 12VDC power input
11. Power switch
12. GND

For more information please contact Protection Depot

Toll Free: 1-877-669-6368 - Email: sales@protectiondepot.com